



# हिमाचल प्रदेश केन्द्रीय विश्वविद्यालय Central University of Himachal Pradesh

धर्मशाला, जिला - कांगड़ा, हिमाचल प्रदेश - 176215  
Dharamshala, District Kangra (HP)-176215

Ref. No: 07/2025-26/CUHP/ENGG/NIQ

Dated: 18.02.2026

## **NOTICE INVITING QUOTATION**

For and on behalf of Central University of Himachal Pradesh, sealed Quotations are hereby invited by the undersigned for the work of **"C/o Toilet in the office of Finance Officer, flooring/cladding in cleaning area, GI roof extension and other repair maintenance works in Admin Block, CUHP, Dharamshala (SH: Tilework, Sanitary installations, Drainage, Water supply, Roof extension, Paintwork etc.)"** from contractors/firms enlisted/ empaneled with Central/ State Govt. Organization/ Central Autonomous body/ Central Public Sector Undertaking as per schedule attached at **Annexure-II**. The sealed envelope containing quotation shall be superscribed with the **Name of Work, Quotation Enquiry Ref. No. and Date** and shall reach the O/o "Executive Engineer(C), CUHP (Construction site), Khabli Dosarka, Dehra, Distt. Kangra, H.P. - 177101" by registered post or delivered personally latest by **02.03.2026 upto 02:00 PM** and shall be opened on the same day at **02:30 PM** in the **"O/o Executive Engineer (C), CUHP (Construction site), Khabli Dosarka, Dehra, Distt. Kangra, H.P. - 177101"** in the presence of intending bidders/contractors or their authorized representatives.

Application for Quotation Document must be accompanied with the self-attested copies of the following qualifying documents:

- 1.) GST certificate.
- 2.) PAN Card.
- 3.) Certificate of enlistment with Central/State Govt. Organization/Central Autonomous body/Central Public Sector Undertaking.
- 4.) Signed copy of terms & conditions (Annexure-I)
- 5.) Schedule of quantities (Annexure-II)

**The approximate cost of the work is Rs. 1,54,241 /- (Rupees One Lakh Fifty Four Thousand Two Hundred Forty One only).**

Detailed quotation document can be downloaded from the University website ([www.cuhimachal.ac.in](http://www.cuhimachal.ac.in)).

-sd-

**Executive Engineer**

Central University of Himachal Pradesh  
Dehra, DisttKangra. Himachal Pradesh

Copy to:

1. Notice board.
2. University Website.

-sd-

**Executive Engineer**

**Terms & Conditions:**

1. The work is to be completed within **40 days**, to be reckoned from the 3<sup>rd</sup> day from date of award of work.
2. The quantities of work in the schedule (refer **Annexure- 'II'**) are provisional and likely to vary (increase or decrease).
3. The prices quoted should be net inclusive of CP&OH charges, freight, Labour, T&P, Cartage, Lead/Lift and GST and nothing extra is to be paid.
4. Security Deposit @ 2.5% of the final work done amount shall be deducted from the bills. This amount shall be released to the contractor after a period of six months from the completion of work.
5. Bidders are advised to visit the site before quoting the rates to assess the quantum and scope of work.
6. Payment shall be made only after the work is completed as per actual quantity and quantum of work executed satisfactorily; no advance shall be paid.
7. All material to be used on the work will have to be got approved from the Engineer-in-charge.
8. Compensation of delay of work will be @ 0.5% per day.
9. The quotation for the work shall have validity for a period of 60 days from the date of opening of quotations.
10. The contractor/firm has to abide by labour rules and regulations.
11. All applicable Taxes and Statutory Deductions shall be deducted from the final bill.
12. In case of any dispute, the decision of Vice-Chancellor, CUHP is final and binding on the contractor.
13. The Central University of Himachal Pradesh reserves the right to accept or reject any or whole quotation without assigning any reason thereof.
14. The firm/contractor shall be responsible for faithful compliance of the terms and conditions enunciated in this document. In the event of any breach of any of the terms and conditions, the assigned work may be terminated and further the work order may be got executed from another agency at risk and cost of the firm/Contractor.
15. In case of any queries/doubts the bidder(s) can visit/contact in the Office of Executive Engineer, CUHP (Construction site), Khabli Dosarka, Dehra, Distt. Kangra, H.P. – 177101 (Mob. 9459240775).

**-sd-**

**Executive Engineer**

Central University of Himachal Pradesh  
Dehra, Distt. Kangra, H.P.

I acknowledge that I have read, and do hereby accept the terms and conditions contained in this quotation document.

Signature with date of bidder

Name (CAPITAL): \_\_\_\_\_

Address:

Contact no:

### **BILL OF QUANTITIES**

<b>Name of Work: C/o Toilet in the office of Finance Officer, flooring/cladding in cleaning area, GI roof extension and other repair maintenance works in Admin Block, CUHP, Dharamshala. (SH: Tilework, Sanitary installations, Drainage, Water supply, Roof extension, Paintwork etc.)</b>					
<b>Name of Bidder:</b>					
<b>S. No.</b>	<b>Description</b>	<b>Unit</b>	<b>Quantity</b>	<b>Rate (Rs.)</b>	<b>Amount (Rs.)</b>
1	Excavating trenches of required width for pipes, cables, etc including excavation for sockets, and dressing of sides, ramming of bottoms, depth upto 1.5 m, including getting out the excavated soil, and then returning the soil as required, in layers not exceeding 20 cm in depth, including consolidating each deposited layer by ramming, watering, etc. and disposing of surplus excavated soil as directed, within a lead of 50 m : All kinds of soil: Pipes, cables etc. exceeding 80 mm dia. but not exceeding 300 mm dia	m	7.80		
2	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacturer), of approved make, in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer in-Charge, in skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement : 3 coarse sand) and jointing with grey cement slurry @ 3.3kg per sqm, including pointing in white cement mixed with pigment of matching shade complete.	sqm	17.17		
3	Structural steel work riveted, bolted or welded in built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	kg	101.34		
4	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:2:4 (1 Cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 40 mm nominal size derived from natural sources)	cum	0.232		
5	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in foundation and plinth in: Cement mortar 1:4 (1 cement : 4 coarse sand)	cum	0.332		
6	Providing and laying Ceramic glazed floor tiles of size 300x300 mm (thickness to be specified by the manufacturer) of 1st quality conforming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 Cement : 4 Coarse sand), Jointing with grey cement slurry @ 3.3 kg/sqm including pointing the joints with white cement and matching pigment etc., complete.	sqm	4.67		
7	Providing and fixing precoated galvanised iron profile sheets (size, shape and pitch of corrugation as approved by Engineer-in-charge) 0.50 mm (+ 0.05 %) total coated thickness with zinc coating 120 grams per sqm as per IS: 277, in 240 mpa steel grade, 5-7 microns epoxy primer on both side of the sheet and polyester top coat 15-18 microns. Sheet should have protective guard film of 25 microns minimum to avoid scratches during transportation and should be supplied in single length upto 12 metre or as desired by Engineer-in-charge. The sheet shall be fixed using self drilling /self tapping screws of size (5.5x 55 mm) with EPDM seal, complete upto any pitch in horizontal/ vertical or curved surfaces, excluding the cost of purlins, rafters and trusses and including cutting to size and shape wherever required.	sqm	6.72		
8	12 mm cement plaster of mix : 1:4 (1 cement: 4 fine sand)	sqm	1.92		
9	Distempering with 1st quality acrylic distemper, having VOC (Volatile Organic Compound ) content less than 50 grams/ litre, of approved brand and manufacture, including applying additional coats wherever required, to achieve even shade and colour: Old work (one or more coat)	sqm	215.43		

10	Providing and fixing white vitreous china pedestal type water closet (European type W.C. pan) with seat and lid, 10 litre low level white P.V.C. flushing cistern, including flush pipe, with manually controlled device (handle lever), conforming to IS : 7231, with all fittings and fixtures complete, including cutting and making good the walls and floors wherever required : W.C. pan with ISI marked white solid plastic seat and lid	no	1.00		
11	Providing and fixing wash basin with C.I. brackets, 15 mm C.P. brass pillar taps, 32 mm C.P. brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require: White Vitreous China Flat back wash basin size 550x 400 mm with single 15 mm C.P. brass pillar tap	no	1.00		
12	Providing and fixing 8 mm dia C.P. / S.S. Jet with flexible tube upto 1 metre long with S.S. triangular plate to European type W.C. of quality and make as approved by Engineer - in - charge.	no	1.00		
13	Providing and fixing mirror of superior glass (of approved quality) and of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing : Rectangular shape 453x357 mm	no	1.00		
14	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC) pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer in Charge. Internal work - Exposed on wall : 20 mm nominal dia Pipes	m	54.00		
15	Cutting holes up to 30x30 cm in walls including making good the same: With common burnt clay F.P.S. (non modular) bricks	no	1.00		
16	Providing and fixing C.P. brass bib cock of approved quality conforming to IS:8931 : 15 mm nominal bore	no	1.00		
17	Providing and fixing C.P. brass angle valve for basin mixer and geyser points of approved quality conforming to IS:8931; 15mm nominal bore	no	3.00		
18	Providing and laying cement concrete 1:5:10 (1 cement : 5 coarse sand : 10 graded stone aggregate 40 mm nominal size) up to haunches of S.W./UPVC pipes including bed concrete as per standard design : 100 mm diameter S.W./UPVC pipe	m	7.80		
19	Making connection of drain or sewer line with existing manhole including breaking into and making good the walls, floors with cement concrete 1:2:4 mix (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) cement plastered on both sides with cement mortar 1:3 (1 cement : 3 coarse sand), finished with a floating coat of neat cement and making necessary channels for the drain etc. complete: For pipes 100 to 250 mm diameter	each	1.00		
20	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS:733 and IS:1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately). For fixed portion: Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	kg	27.91		

21	Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS:733 and IS:1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately). For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately): Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)	kg	5.41		
22	Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868 ) transparent or dyed to required colour or shade, with necessary screws etc. complete : 150x10 mm	no	2.00		
23	Providing and fixing aluminium handles 125 mm, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete.	no	2.00		
24	Providing and fixing 4 mm thick ACP sheet exterior grade in panelling fixed in aluminum doors, windows shutters and partition frames with EPDM rubber / neoprene gasket etc. complete as per architectural drawings and directions of engineer-in-charge.	sqm	8.99		
25	Providing and laying UPVC pipes in underground drainage work with necessary fittings, solvent etc. complete : (i) Single socketed pipes : 110 mm diameter	m	16.50		
26	Providing and fixing stainless steel curtain rod having wall thickness of 1.20 mm with two stainless steel brackets fixed with C.P. brass screws and PVC sleeves etc., wherever necessary complete : 25 mm dia.	m	2.80		
27	Providing & fixing curtains of size 4x7 feet approx. made up of polyester heavy fabric including top belt of 100 mm width with inbuilt SS metallic rings, bottom fold of 150 mm width, complete.	no	3.00		
		Total (in Rs.)			
	Total Amount in Words:				

-sd-  
**Executive Engineer**  
Central University of Himachal Pradesh  
Dehra, Distt. Kangra, H.P.

**Signature of bidder**

**Name:** \_\_\_\_\_

**Address:**\_\_\_\_\_